



ca prima



CA Prima: industrial vacuum cleaners equipped with powerful top-mounted motors

The CA Prima vacuum cleaners range combine the power of two-stage bypass motors with the robust frame of an industrial vacuum cleaner.

They are vacuum cleaners equipped with 2 or 3 motors that deliver an excellent air flow rate.

The dedicated filtration chamber of the CA Prima vacuum cleaners ensures filtration surface area.

The CA Prima vacuum cleaners range can work in different sectors and are suitable for different applications in industrial, automotive, artisans, transport and logistics sectors.

KEY FACTORS OF THE CA PRIMA RANGE

- Multifunctional: a range of vacuum cleaners designed to tackle a great variety of applications.
- The power of the two-stage bypass motors in a robust industrial structure.
- Multiple motors (2 for CA Prima 2PS and 3 for CA Prima 3M) that combine to deliver an excellent air flow.
- The dedicated filtration chamber ensures maximum filtration surface area.
- Wet vacuum function (optional) through liquid level detection mechanisms.
- The CA Prima 3M steel head is indestructible. Great for rentals.
- Robust steel frame.
- Wheels with brake.
- Practical accessory holder.
- Equipped with star-shaped polyester class L filter. All filter classes and types available on demand.



MODELS

CA Prima 2PS

Tank capacity: 40 l

Type: industrial

Suction: motors

CA Prima 3M

Tank capacity: 60 l

Type: industrial

Suction: motors

Powerful vacuum cleaners that can be adapted to different applications for environments in the industrial sector



CA Prima are the ideal industrial vacuum cleaners to facilitate and speed up cleaning operations in production environments. They increase efficiency, while making workplaces safe and save money.



The main need for those who use industrial vacuums in production environments is to quickly remove large quantities of dust, so as not to hinder normal working activities. CA Prima are industrial vacuum cleaners designed to provide a professional, fast and reliable vacuuming solution.

Details that matter:



TANGENTIAL VACUUM INLET

Creates a vortex of the incoming dust, helps to keep the filter clean and protected.

INTERNAL CYCLONE CONE

It further protects the filter against dust and debris.

Filters available in different classes (optional):

Class L

Class M

Class H Hepa with PTFE membrane



EASY EXTRACTION OF THE LOWER TANK

CA Prima 3M is equipped with a detachable tank on wheels to facilitate the moving and emptying of the recovery tank.

PEEPHOLE FOR CHECKING THE FILLING LEVEL OF THE LOWER TANK

FILTER SHAKER

The autonomous filter shaking mechanism makes it vibrate continuously during use. Practical filter shaker knob positioned on the tank.



STEEL HEAD

The head of CA Prima 3M is made of steel to make it indestructible. Great for rentals.

ROBUST VACUUM CLEANERS

Robust steel frame.

Wheels with brake.

Practical accessory holder.

REFERENCE SECTORS



Industrial



Cleaning
contractors



Handicraft



Automotive



Large-Scale
Retailing



Logistic



Transport

Kit and accessories available for CA Prima



217177 Standard kit - Ø40 mm

◊



217178 Extra kit Ø40 mm

◊



217180 Standard kit Ø50 mm

◊



217181 Extra Kit Ø50 mm

◊



217182 Antistatic kit Ø40 mm

◊



217183 Antistatic kit Ø50 mm

◊



217184 Standard oven kit Ø40 mm -
max 125 ° C

◊



400999 Hose: evaflex - Ø40 mm

◊



401000 Hose: evaflex - Ø50 mm

◊



401008 Hose: Oregon - polyurethane,
antistatic, oilproof - Ø40 mm

◊



401009 Hose: Oregon - polyurethane,
antistatic, oilproof - Ø50 mm

◊



400997 Hose: Evaflex - polyurethane,
antistatic, oilproof - Ø50 mm

◊



427167 Hose: Oregon - heat resistant -
25 ° C up to 125 ° C - Ø40 mm

◊



422492 Hose: Oregon - heat resistant -
25 ° C up to 125 ° C - Ø50 mm

◊



412509 Hose: Steel - Ø40 mm

◊



426769 Hose: Steel - Ø50 mm

◊

Legend

• standard ◊ optional

Kit and accessories available for CA Prima



405422 Star filter - polyester, class L

•



405423 Star filter - heat up to 200°C,
class L

◊



405424 Star filter - antistatic, class L

◊



417435 Pre-filter nylon with
non-stick surface

◊



445659 Pre-filter - polycarbonate with
non-stick surface

◊



2222272 HEPA cartridge filter kit -
class H14

◊



204614 Electronic float kit for
single-phase models (must be installed
during manufacturing)

◊



400579 Reducer 70> 50 steel

•

Legend

• standard ◊ optional

TECHNICAL DESCRIPTION		CA Prima 2PS	CA Prima 3M
Voltage-frequency	V-fase-Hz	230-1-50/60*	230-1-50/60*
Power	W-Hp	2400	3600
Motor	n./type	2/double stage bypass	3/double stage bypass
Water lift	mmH ₂ O/inchH ₂ O	2500	2500
Airflow	m ³ /h / feet ³ /h	430/1410,76	650/2132,55
Tank capacity	l/gal	40/10,56	60/15,85
Filtration surface area	cm ² /inch ²	19500/7677,16	19500/7677,16
Noise level	dB	72	73
Dimensions (Lxhwx)	mm/inch	610x1150x850/24x45,27x33,46	640x1320x870/25,19x51,96x34,25
Weight	Kg/lbs	63/138,89	85/187,39

*other voltages available on request



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

